

cho

fms

Survey made to establish corners of P. S. Wilsons Homestead claim in section one, T9S, R27E

It being required to find the centre of section one I qualified on oath George Stubblefield and Thomas Brierly as assistants and proceeded by ranging out a line from $\frac{1}{4}$ section corner on range line east of Section One to $\frac{1}{4}$ section corner on west boundary of Section one. also ranged out line from $\frac{1}{4}$ sec corner on South boundary of section one to $\frac{1}{4}$ sec cor on North boundary of section one (all of which $\frac{1}{4}$ section corners were in good condition (size and position according to United States field notes) and at intersection of ranged line I placed a stone $8 \times 9 \times 11$ inches marked $\frac{1}{6}$ _{CS} for centre of section and buried broken glass bottles 18 inches deep beneath stone

43 00

I then ran west on true line to $\frac{1}{4}$ cor on West boundary of section and find the distance to be

and the magnetic bearing of the line to be $S 68^{\circ} W$

$S 68^{\circ} E$

$S 68^{\circ} E$ retracing same line

21 50

placed stone $8 \times 10 \times 14$ marked $\frac{1}{6}$ _{CS} and buried broken glass bottles beneath stone one foot deep.

20 00

I then ran North var 22 East

placed stone $6 \times 8 \times 16$ inches marked $\frac{1}{6}$ _{CS} resting on broken glass bottles buried one foot deep

21 50

Thence $S. 68^{\circ} W$

intersect west boundary of section 18.90 chains South of closing corner to sections 1 and 2

Made April 5th 1895

Clarence Johnson

County Surveyor

By G. F. White Deputy

Recorded May 18th 1895

G. F. White

County Surveyor