

Ch Links

Application having been made by E L McBroome for the subdivision of the West-half Sec 22 Twp 8 S Range 30 E
On the 10th day Sep 1908. Wesley Slaughter and John Silvers were sworn as chainmen

Proceeded to the NW Cor Sec 22 Original Corner missing. found witness tree as described in field notes and established this corner by a Rock set deep in the ground in McBroome's Garden marked with 3 nails on south side, 6x14x7 and confirmed its position by running West to Cor 16, 17, 20, 21 and also E to NW cor of Sec 22 the juniper mentioned as the 1/4 corner in field notes. Witness trees then proceeding to NW Cor Sec 22 Run South

20

set Temporary Corner for No 6 see diagram on plat the numbers in Red indicate the number of the corners of the section

40

1/4 Corner missing set temporary

60

set Temporary corner for No 16

78

75

SW Cor Sec 22 falling East 92.1 lbs

Hence East

20

92

set temporary cor for No 24

39

84

The 1/4 corner

79

68

The SE corner Sec 22 Pile plain falling 130 lbs S

North

37

11

The 1/4 corner of E side Sec 22

79

71

The NE cor of Sec 22 as determined by field notes

West

40

1/4 cor on North side Sec 22 (a juniper tree)

78

50

to the point of beginning the NW Cor Sec 22

Proceeding to Temporary 1/4 cor at West side a run a straight line to opposite 1/4 cor of section and straight line from 1/4 cor to opposite one on South side and at their intersection set center of section. The Red rock close to surface no stones handy to make a monument. All that was for was to witness it by distant pine trees from the center of section. A yellow Pine bears S 78° E. 36' Dia 13 ch 14 lbs. A y Pine bears N 25° (miles) W. 6 ch 18 lbs on the surface

Proceeding to each of the temporary corners connected them. Set marked and witnesses as follows.

6th 1/4 Corner a Rock 8x7x10 set deep marked 1/4 cs, 15th 1/4 Corner on 1/4 corner on West side a Rock 7x9x10 set deep marked 1/4 cs. A y Pine bears S 28° W 407 lbs. A y Pine bears S 52° 15' W 274 lbs, 16th 1/4 Corner A solid fixed Rock marked 1/4 cs A y Pine bears S 43° 30' 24th 1/4 Cor A fixed Rock marked 1/4 cs A y Pine bears S 50° 45' E 290 lbs, 18th 1/4 Cor A Rock 6x8x11 marked 1/4 Built a mound of rocks 8th 1/4 Rock 7x6x12 marked 1/4 cs, 4th A Rock 5x7x10 marked 1/4 cs

Then Proceeding to No 4th corner run a straight line to Cor 24 see diagram red figures, And straight lines from 16 to 18 And from 6 to 8 and at the different intersections of these lines set the permanent corners of 7 and 17

Corner of 17 is a Rock 5x7x9 dug Pits

Corner of 7 a Rock 5x6x8 marked 1/4 cs from which a y Pine 36' Dia bears W 78 lbs. Marked with 3 nails on each side East and West

Total Costs were \$19 Nineteen Dollars for Field Notes and My Fees

Chainmen and Stakemen were paid

And the whole Site was paid by E L McBroome

Sep 14, 1908.

Michael Spears County Surveyor