"1" Page 131 Book Dated at Bend, this 19

I found evidence of the .... SOUT. township .18...S. one-quarter corner neridian ... of section 34 original location of this comer. as described hereon; and that from this evidence I established a new described hereon to perpetuate the monument and W.M. range 26 E accessories as

\*DIAGRAM

State of Oregon County of .Deschutes... Laurence C. Stratton History of original corner establishment:

oo nereby certify that on the 19 day of MKK AUE , 19 62

Description of corner

Found mound of stone and stake set by U\*S.F.S. for approximate corner. This was not accepted as true corner. Location of corner by this survey was set at mid point distance between opposite section corners along south boundary of section.

original location of this corner Description of manument and accessories I established to perpetuate the

Signature Civil Engineer.
Title Civil Engineer.
4563

qual State

down oct

1962

Oregon

Set 2" iron pipe with brass cap stamped as per BLM manual for the survey of the public lands. From the corner I set two bearing trees as follows:

A 15" pp bears N53°E 23 feet and a 21" PP bears S 23° W 25feet

#48904

urence C. Stratton., known

said state, personally appeared

to me to be the person whose name is

ibscribed to the within instrument and

Who acknowledged to me that he exe-

on this 19 day of Oct before me, a natary public in and for

County of .

Deschutes ) 55.

1962

State of Oregon.

/ VISEAL!

riginal

NOTARY PUBLIC

buted the same.

Residing of Bend, Cregon

Commission expires Day 36, 1966

Form R6-5680-182

......, 19....., at....... o'clock .....m., (signed) for record on the ...... day of ...... (DEPUTY) (COUNTY OFFICIAL)

CERTIFIED RECORD OF LAND CORNER MONUMENTATION (Reference FSH 5681.65)

Original corner was established by Alonzo Gesner under contract no. 206 dated July 10, 1874. Original monument was 14x10x4 stone. No

1874. Original monument bearing trees were set.