No.

10 30 JEV

Form R6-5680-182

CZ:

NOTARY . 60 Br. C. j **#53**864 Page 158 Commission expires 9 18.65 Residing oHarney...County,...Ore... to me to be the person whose name is before me, a notary public in and for On this 16 thboy of November ..., 19 64 County of Harney Signord Marcelles at Malore I found evidence of the corner do hereby certify that on the 2nd day of June , 19 64. cuted the same. State of Oregon who acknowledged to me that he exesaid state, personally appeared Title Land Surveyor.
Registration No. 350 Dated of Burne, Oregon / Harsellum A. Palmer. County of .. Harney ... State of Oregon meridian subscribed to the within instrument and Marcellus A. Palmer , known rownship 195. *DIAGRAMq" PP common to sections 14, 15, described hereon to perpetuate the as described hereon; and that from arum original location of this comer. this evidence I established a new nonument and accessories 16they of November Willame tte. NOTARY PUBLIC range26E..... Miniman 75 67) S.S. ř

Corner stone above desribed found.

Description of corner evidence found:

Marked stone $1L \times 10 \times 8$ found. A B.T. was found scribed T19SR26E S1L, bearing almost due E from corner. Evidence indicated original P.T. destroyed by fire. B.T found was apparently put in about 1900 by the ring count.

original location of this corner Description of manument and accessories I established to perpetuate the

Monument set consists of a $2\frac{1}{2}$ brass disk welded to a 2 galvanized from pipe withan 8 square piece of flat from welded to its bases, approximately 30 in length, buried approximately 20 in the ground with a mound or rock surrounding it. Disk is stamped with Metal dies; as follows:

T198 R26E

15 14

From which:

A 10" P,P. bears N 13°20'E, 12.5 Lks

A 7" P.P. bears S64°30'E . 97.66 Lks

A 5" P.P. bears S67°55'W, 18 Lks

A 9" P.P. bears N12°35'W, 87.5 Lks

Scribing on the old B.T. was obliterated.

CERTIFIED RECORD OF LAND CORNER MONUMENTATION (Reference FSH 5681.65)

T. 19 S., R. 26 E. W.M. See Corner common to 14-15-22-23

History of original corner establishment:

Original contract survey for G.L.O. made in August, 1874.
Original corner was a marked stone 16 x 12 x 8 from which
a pine bears 8 35 E, a distance of 48 links.

by Slaw Campbell, (DEPUTY)