No.

T. 16 S., R. 26 E. Section 32 W 1/16 on E-W Center Line w1/45 Dared a Bur s Oregon day of August ,19 64

from d evidence of the I established a monument as described hereor for the W 1/16 corner on the County of ....Harney... do hereby certify that on the... "Marcellus A. Palmer State of ... DIAGRAM described horoon to perpetuate the Location of this comer. Oregon line of Section 32 MON. AT

#538**3**4 Page 163

Statemegon )

County of Harney | 555

On this 16 they of lovember | 16! before me, a notary public in and for said state, personally appeared

Residing offlerively County, Greecommission expires  $\mathcal{GMSLS}$ Melle Harry

Form R6-5680-182

this 16thday of Navember 184 signapor Machine

Registration No. 350 Title Land Surveyor

Earcellus A. Palmer to me to be the person whose name is who acknowledged to me that he exesubscribed to the within instrument and ..., known

original location of this corner Description of monument and accessories I established to perpetuate the

Monument consists of a  $2\frac{1}{6}$  inch trass disk welded to the tom of a 2 inch galvenized from pipe, approximately 30 inches in length, turied approximately 20 inches in the ground with a mound of rock set around the base. Flat piece of steel is welded to the base of the monument.

ORB 350 1 % 1 C T16S 9<u>1</u> 16 ن 32 R26E

Disk is stamped with metal dies as follows

CERTIFIED RECORD OF LAND CORNER MONUMENTATION (Reference FSH 5681.65)

History of original corner establishment:

4th

Interior corner, not established previously

Description of corner evidence found:

Established by proportionment between  $\frac{1}{4}$  section corners, established in P.L.X. Dependent Resurvey of 1950.

Office of ..... .....County of .... State of ......., I hereby certify that the within instrument was filed in this office for record on the ...... day of ..... (COUNTY OFFICIAL)