No.

T. 16S R.26E.
Section 34
S 1/16 on N-S C.L.

	Residing affarney county, Ore. Commission expires 9.16.65	
Disk is stamped with metal dies as follows	MENUM E SULLEGAS	
	subscribed to the within instrument and who acknowledged to me that he executed the same.	
Imprely 20 inches in the ground with a moun Flat piece of steel is welded to the base o	Marcellus A. Palmer , known to me to be the person whose name is	
onsists of iron pice,	#: said state, personally appeared	
original location of this corner	State of Oregon) County of Harney) County of Harney) On this 16th day o November 1964	
	Title Land Surveyor Registration No. 350	
	Dated of Burns, Orean this 16theory of November 1964	
established in B.L.E. Dependent Resurvey of previously established during the course of the course o	s ts	
	Mon at Min A	
Description of corner evidence found:	-	
	described hazaon to perpetuate the original location of this comer. *DIAGRAM • C \(\subseteq \)	
	this evidence Lestablished a new	
	for the south 1/16 corner on center line of Section 34. hownship 168 range 26E meridian Willamette	
S. 1/16 on N-S Center Line Interior corner, not established previous	do hereby certify that on the 24th day of July 19 64 Hound evidence of the I established moniment of december 19	
History of original corner establishment:	, Marcellus A. Palmer	4
(Reference FSH 5681.4	State of Oregon) County of Harney , ss.	
CEDTICIES DECOST OF LAW CORNE		

CERTIFIED RECORD OF LAND CORNER MONUMENTATION (Reference FSH 5681.65)

1 # 1

1/16 on N-S Center Line terior corner, not established previously.

blished by single proportionment between 1/4 section corner blished in B.L.W. Dependent Resurvey of 1960, and the Casiously established during the course of this survey.

nt consists of a $2\frac{1}{2}$ inch brass disk welded to the top of a 2 inch sized iron pice, approximately 30 inches in length, buried approxy 20 inches in the ground with a mound of rock set around the base.

S 0kE 350 T168 ،0 196<u>4</u> **H26E** S 34

(COUNTY OFFICIAL)