T. 16S., R. 26E. Section 33 W 1/16 on N-S C.L.

Same of Oregon County of Harney

do hereby certify that on the , larcellus A. Palmer

day of August

..., 19...

64

♦ C 4 S

Page 169 "A"

County of Harney. State of Oregon before me, a notary public in and for said state, personally appeared

#53864

to me to be the person whose name is subscribed to the within instrument and who acknowledged to me that he exe-

this 16thday offlowember 19.64 Signary Medle Offilian Dated at Eurns, Oregon

On this 16thoy of Maxemb er., 19.61 Registration No. 350 Title Land Surveyor ...) ss.

Marcellus A. Palmer

Residing offerney County, Ore.

Form R6-5680-182

CERTIFIED RECORD OF LAND CORNER MONUMENTATION (Reference FSH 5681.65)

History of original corner establishment:

N. 1/16 on N-S Center Line Interior corner, not established previously.

penter line of Section 33.

wonument as described hereout the north 1/10 corner on

meridian Willamette

Description of corner evidence found:

MON. SET

original location of this comer.

described hereon to perpetuate the this evidence I established a new as described hereon; and that from monument and accessories as

*DIAGRAM

* N+S

Established by single proportionment between a section corner established in B.L.W. Dependent Resurvey of 1960, and CaS previously established during the course of this survey.

Description of monument and accessories I established to perpetuate the

original location of this corner

Conument consists of a $2\frac{1}{2}$ inch brass disk welded to the top of a 2 inch galvanized iron rine, approximately 30 inches in length, butled approximately 20 inches in the ground with a mound of rock set around the base. Flat piece of steel is welded to the base of the monument.

N 17 T168 S 33

, I hereby certify that the within instrument was filed in this office

(COUNTY OFFICIAL)

for record on the

(DEPUTY)

Disk is stamped with metal dies as follows

1964