

Proceed to SW Cor. Sec 22 South on Random
 20 set fence 1/4
 40 1/4 Cor. Minnie
 80 36 The SW Cor. Sec 27 full E 92 lks which is a large Rock right on the West Bank North of fence running E & W. Thence East
 41 50 The 1/4 Cor. (ie S 1/4 Cor 27) Thence E
 42 62 The SE Cor. Sec 27 full S 174 lks North
 40 62 The E 1/4 Cor. Sec 27

Proceeded to NE Cor. Sec 27 Ran S
 20 set fence 1/4 Cor. South
 41 The E 1/4 Sec 27

After Establishing the North & South 1/4 Corners of Sec 22 by the W 1/4 Cor. Sec 27 Draw a straight line from opposite 1/4 Corners across the Sec. 22 & 27 setting Temp 1/4 Corners every 20 Ch. at the intersection of these lines after correcting them to their true line and set the Temp 1/4 on true line and half way from true center to the corresponding 1/4 Corners. I placed the Centers of Sec 22 & 27 and established them permanently also the 1/4 Corners that were called for in the application

Dated of Witness to Corners and descriptions thereof See Plat for Numbers of 1/4 Corners referred to
 Corners of Sec 22

North 1/4 Cor. Marked 1/4 CS 16x17. set deep 2 inches above ground in a mound of Rocks

North W Cor. A Rock 14x6x7. Tapering Marked 111 on each edge and CS set in deep corner near SW corner about 16 feet from fence. An old Emancip (ie NE corner) bears S 75° 10' 31" E 31 lks. A ledge of Rocks on point (NW & SE)

Marked a Solid Rock of this ledge CS which bears from the NW cor Sec 22 North 54° E 354 lks

South 1/4 Cor. Sec 22 A Rock 12x8x4 set deep in ground in stubble field. The East terminus of division line of the Estate which is 16 ch SW from the bridge bears S 51° 30' E 342 lks

Center of 22 A Boulder 12x4x6 Marked +CS at foot of Irish stump A 1/2 pine (2 Double) 18' Dia 36' Dia bears due W 142 lks
 Sixteenth Corners 1, 2, 3, 4, 5, 6, 7, 8 not called for

" " No 9 A Marked Rock planted right at corner of hanging wire fence which runs North & South running East

" " " 10 Boulder buried deep from which a Cottonwood 12' bears North 31° East 30 lks

" " " 11 Rock set in stubble field on true line from opposite 1/4 corner on E & W side of the 1/4 ac

" " " 12 Boulder close to West Bank in mound of boulders A Cottonwood bears S 33° 45' W 34 lks

" " " 13, 14 not called for

" " " 15 This point was determined accurately to determine the center of NE 1/4 Sec 27 but was not established as all the land on north side of river belongs to J. Deardorff and this corner did not affect him

" " " 16 A Rock 12x6x8 with mound of rocks. 23 lks S of center of Cont. Road in securation

Dated of Corners of Sec 27. The North East Corner is buried. A 1/2 pine bears S 20° 45' E 124 lks
 A 1/2 pine 8' Dia bears S 14° E 114 lks

North 1/4 Cor. See above data of S 1/4 Cor. Sec 27

W 1/4 " Sec 27 Rock 18x10x6 set deep to bed rock in mound of rocks

1/4 Corners No 15 & 16 see data of Sec 22

" " No 3 Rock 12x4x4 in mound of rocks

" " " 4 Rock 12x12x4 set deep projecting a little above ground in timothy meadow

" " " 5 Rock 9x8x7 in mound of rocks

" " " 6 A Rock 12x7x6 Boulder on East side of fence about 40 lks in timothy meadow. A 1/2 pine 24' Dia bears N 66° E 990 lks

" " " 7 Determined but not established no call under circumstances

" " " 8 Rock 4x9x7 in mound of rocks

" " " 9 Rock 12x10x8 set in ground mound of rocks

" " " 10, 11, 12, 13, 14, 15, 16 not called for in Application

Variation of Needle 19° E Lat used 44° 23' Dec Oct 27 1908 = 72° 31' (Ref. subtracted)

Survey began Oct 27¹⁹⁰⁸ at 1 P.M. Ended

Continued next Sheet

Michael Spears C.S. Nov 16 1908