

173 A.


T. 16S R. 26E.
Section 30
E 1/16 on E-W C.L.

CERTIFIED RECORD OF LAND CORNER MONUMENTATION
(Reference FSH 5681.65)

History of original corner establishment:

E. 1/16 on E-W Center Line
Interior corner, not established previously.

I, Marcellus A. Palmer
do hereby certify that on the 15th
day of January, 1964,
I found evidence of the established
monument as described hereon
for the East 1/16 corner on
center line of Section 30.
township 16S range 26E.
meridian Willamette
as described hereon, and that from
this evidence I established a new
monument and accessories as
described herein to perpetuate the
original location of this corner.
*DIAGRAM



Description of corner evidence found:

Established by single proportionment between 1/4 section corner
established in F.L.W. Dependent Resurvey of 1960, and the C 1/4 S
previously established during this survey.

Dated at Burns, Oregon
this 16th day of November 19 64
Signature *Marcellus A. Palmer*
Title Land Surveyor
Registration 250

Description of monument and accessories I established to perpetuate the
original location of this corner

Monument consists of a 2 1/2 inch brass disk welded to the top of a 2 inch
galvanized iron pipe, approximately 30 inches in length, buried approx-
imately 20 inches in the ground with a mound of rock set around the base.
Flat piece of steel is welded to the base of the monument.

T16S R26E
C 1/16 S 30
ORE 350 1964

Disk is stamped with metal dies as follows

Marcellus A. Palmer
(SEAL)
NOTARY PUBLIC
Residing at Harney County, Ore.
Commission expires 9-18-65

Form RC-5680-182

Office of _____ County of _____
State of _____, I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19____, at _____ m., o'clock _____ m., (signed)
by _____ (COUNTY OFFICIAL)
(DEPUTY)