No.

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

(Reference FSH 5681.65)

History of original corner establishment:

Center 1 Section corner

Interior corner, not established previously

Description of corner evidence found:

Established by single propertionment between  $\frac{1}{2}$  section corners established in F-L-%. Dependent Resurvey of 1960

original location of this corner Description of monument and accessories I established to perpetuate the

Monumented consists of a  $2\frac{1}{2}$  inch brass disk welded to the top of a 2 inch galvanized iron pipe, approximately 30 inches in length, buried approximately 20 inches in the ground with a mound of rock set around the base. Flat piece of steel is welded to the base of the monument.

T168 R26E

C AP S

Disk is stemped with metal dies as follows

28

02350 1964

State of

Office of (COUNTY OFFICIAL)

Title Land Surveyor Signatur

before me, a notary public in and for On this 16 thday of ... November., 19.6 State of .....Oregon said state, personally appeared County of Harney

ss.

#53864

to me to be the person whose name is subscribed to the within instrument and who acknowledged to me that he exe-Marcellus A. Palmer, known

PUBLI Form R6-5680-182

HOTAR

Commission expires A 1865 Residing or Harney County, Ore. NOTARY PUBLIC. T. 16S., R. 26E. Section 28