No.

. 19 64

21 th

not established previously.

South 1/16 Section corner on N-S Center line,

CERTIFIED RECORD OF LAND CORNER MONUMENTATION (Reference FSH 5681.65)

History of original corner establishment:

meridian.....Willamette *DIAGRAM C S as described hereon; and that from this evidence-Lestablished a new described hereon to perpetuate the .. range .. 26E.

Wor at A

Dated at Durns, Oregon Marcelles 11 \$15

to me to be the person whose name is subscribed to the within instrument and Marcellus A. Palmer , known

Commission expires ... Residing or Harney County, Ore. NOTARY PUBLIC 9.1865

177 Page

Registration No. 350 County of Harney State of Oregon Title Land Surveyor

On this 16 thuny of November before me, a notary public in and for said state, personally appeared 1961

#53864

who acknowledged to me that he exe-Win

this 16th day oflowembor.

original location of this corner

Description of monument and accessories I established to perpetuate the

Description of corner evidence found:

Established by single proportionment between 1/4 sedtion corner established in B.L.M. Dependent Resurvey of 1960. and the C_4^2S previously established during this survey.

Monument consists of a $2\frac{1}{2}$ inch brass disk welded to the tom of a 2 inch galvanized iron pipe, approximetly 30 inches in length, buried approximately 20 inches in the ground with a mound of rock set around the base. Flat piece of steel is welded to the base of the monument.

s 171 T16S R26E s 27

Disk is stamped with steel dies as follows

for record on the day of

Form R6-5680-182

03**5**50

1964

Office of

(DEPUTY)

(COUNTY OFFICIAL)