







State of **Oregon**.....)  
County of **Harney**.....) ss.

I, Marceline A. Palmer  
do hereby certify that on the 16th  
day of July, 1964

Home evidence of the established monument as described hereon for the Northwest 1/16 corner of Section 25.  
Township 16S. Range 26E.

meridian. WILLAMETTE  
as described herein and that from  
this evidence I established an  
monument and accretions of  
described herein to perpetuate the  
original location of this corner.  
\*DIAGRAM      

N.W.  $\frac{1}{4}$  SEC.  
N $\frac{1}{2}$ M $\frac{1}{2}$ A $\frac{1}{2}$   
Mo $\frac{1}{2}$ NT  
CENTER  
N $\frac{1}{2}$ E  
Mo

Mon  $\frac{1}{2}$  S  $\frac{1}{2}$  W  $\frac{1}{2}$  Mon  $\frac{1}{2}$  C  $\frac{1}{2}$  S  $\frac{1}{2}$  Mon  
 Dated at Burns, Oregon.....

Signature *William C. J. ...*  
Title Land Surveyor  
Registration No. 350

State of Oregon )  
County of Harney ) ss.  
On this 16th day of November, 1964

Marcellus A. Palmer, known to me to be the person whose name is subscribed to the within instrument and who acknowledged to me that he executed the same.

Residing at Harney County, Ore.  
Commission expires 9.18.05

Form R6-5680-182

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**  
(Reference FSH 5681.65)

### History of original corner establishment

Northwest 1/16 Section corner, not established previously.

**Description of corner evidence found:**

Established by single proportionment between 1/16 corners established during the 1960 B.L.M. Dependent Resurvey.

Note BLM Cadastral Survey of 1960 re-established or established exterior corners at evenly proportioned distances. Hence, any N-S or E-W line between opposite corners can be evenly proportioned to locate any interior corner on such line.

**Description of monument and accessories | established to perpetuate the original location of this corner**

Monument consists of a 2½ inch brass disk welded to the top of a 2 inch galvanized iron pipe, approximately 30 inches in length, buried approximately 20 inches in the ground with a mound of rock set around the base. Flat piece of steel is welded to the base of the monument.

T16S R26H

Disk is stamped with steel dies as follows

 $\frac{1}{16}$  NW

OREG 50 1964

Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_, I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_, at \_\_\_\_\_ o'clock \_\_\_\_\_ m., (signed)  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)