No.

Form R6-5680-182

Residing of Harney County, Ore.
Commission expires 9.1565

Commission expires

T. 16S., R.26E. Section 23 S 1/16 on N-S C.L.

| Des | day of July ,19 64 Hound evidence of the I established a monument as described hereon for the south 1/16 corner on center line of Section 23. rownship 16S ronge 26E. meridian Willamette meridian Willamette observation of this corner. **DIAGRAM** **DIAGRAM** | Page 181 |
|-----|---|----------|
| | eby certify that on the | |
| ₩ | <u>ر</u> ک | |
| | State of Oregon | |

Established by single proportionment between $\frac{1}{4}$ section corner established in U.L.W. Dependent Resurvey of 1960, and the $C_{\frac{1}{4}}^{2}$ S previously established during this survey

Description of monument and accessories I established to perpetuate the original location of this corner

#53864

On this 16 they officember 1964

before me, a notary public in and for

said state, personally appeared

to me to be the person whose name is

Marcellus A. Palmer, known

who acknowledged to me that he exesubscribed to the within instrument and

cuted the same.

Whian

NOTARY PUBLIC 3 willed County of Harney

, ss.

State of Oregon

Registration No. ...350 Title Land Surveyor

Conument consists of a $2\dot{\epsilon}$ inch trass disk welded to the top of a 2 inch galvanized iron pipe, approximately 30 inches in length, buried approximately 20 inches in the ground with a mound of rock set around the base. Flat piece of steel is welded to the base of the monument.

Disk is stamped with steel dies as follows 0KE350 s 1 15 1168 _CR26E 1964 s 23

CERTIFIED RECORD OF LAND CORNER MONUMENTATION (Reference FSH 5681.65)

1/2

story of original corner establishment:

S. 1/16 on N-S Center Line

Interior corner, not established previously.

(COUNTY OFFICIAL)