No.

J. 4

Muncillas (1.1) alimon 1964 original location of this corner Description of monument and accessories I established to perpetuate the

subscribed to the within instrument and cuted the same. who acknowledged to me that he exe-

From which:
A 10" Juniber bears N 53° E
An 6" Juniber bears S 79° E
A 7" Juniper bears S 13° W
An 8" Juniper bears N 60° W

76 links 73 links 36 links 60 links

03년 350

7961 og 1981

5-1-

Monument consists of a 2_2 inch brass disk welded to the top of a 2 inch galvanized iron pipe, approximately 30 inches in length, buried approximately 20 inches in the ground with a mound of rock set around the base. Flat piece of steel is welded to the base of the monument. Disk is stemped with wetal dies as follows:

Mone found.

Corner location re-established by double proportionment between the closest adjacent found corners north and south, and east and west

History of original corner establishment:

18**t**h

T. 17S. R 26E.
Section 4
SW Section corner

CERTIFIED RECORD OF LAND CORNER MONUMENTATION (Reference FSH 5681.65)

Original corner set in 1874 by G. L. O. by private contractor. Field notes call for an unmarked rock 14 x 12 x 8. No accessories noted. No other ties in any direction except the closest corners which were quarter section corners. No knowledge of this corner could be obtained from any local resident contacted.

State of ... for record on the day of (COUNTY OFFICIAL) (DEPUTY)

#53864 On this 16they of November , 1964 before me, a notary public in and for

to me to be the person whose name is said state, personally appeared Marcellua A. Palmer

Residing of Harney County, Ore.
Commission expires 9.18.65 Whan TOTARY PUBLIC

Form R6-5680-182