

No.

FOR H. A. Cupper.

TOWNSHIP 7 S. RANGE 27 E. WILL. MER. Gray.

S. P. Walker } Chairman Survey.
 G. S. Howett
 commenced at Sec. cor. for Secs. 3, 4, 9 and 10,
 qualified on oath, S. P. Walker as chairman and
 acting myself as rear chainman and run N. in line
 course and Secs. lines to $\frac{1}{4}$ Sec. cor.
 Find $\frac{1}{4}$ Sec. cor. in good condition, Thence S. on
 same line, placed stone 12x12x17 in., in stone
 mound marked $\frac{1}{4}$ Sept. 2, 1898.

37 27
18 64

80 50

40 23-

42 34
21 17
38 22

Qualified on oath G. S. Howett, chairman, and
 commenced at $\frac{1}{4}$ cor. on line between Secs. 3 and 4,
 and run E. on random line, variation 21° E.
 intersect E. line of Sec. 3, 92 chs. N. of witness cor.
 which is 1,40 chs. N. of true cor. in N. fork of
 John Day River;
 Thence W. from W. c. on offset line parallel to
 true line,
 Thence N. 1,40 chs. to true line; placed stone 14x14x
 16 in., marked thus $\frac{1}{3}$ for centre of Sec. 3, in dry
 bed N. fork of John Day River, from which cotton
 wood tree 12 in. in diameter bears N. 32° 30' W.
 $\frac{1}{4}$ distant.

I then run true line from $\frac{1}{3}$ Sec. cor. on S.
 boundary of Sec. E. to $\frac{1}{4}$ cor. and find distance
 to be at mid way, viz. 21.17 placed tempo-
 rary cor. and run N. to point mid way
 between centre of Sec. at W. $\frac{1}{4}$ post, and find
 distance to be at 19.11 chs. placed stone 18x12x14
 in., marked $\frac{1}{6}$ raised stone mound around cor.
 Made and examined Sept. 2nd, and 3d, 1898.

W. F. White

County Surveyor.