

W.L.Lascall.

feet.

- Started at the South one quarter corner of Section  
(7) seven, township thirteen south range twenty six  
east of Willamette Meridian. thence,
- East
- 2688.0 To the South east corner of section seven same township  
and range as above, Thence,
- North
- 5505.8 To North east corner of section seven, township thirteen  
south range twenty six east of Willamette Meridian. thence
- ~~2652.9~~ South
- 2652.9 To East one quarter corner of section seven, same town  
ship and range, which being obliterated, I establish with  
a basalt stone, chiseled  $1\frac{1}{4}$  C.S. set in a mound of stone.  
thence,
- West.
- 5263.5 To the West one quarter corner of said section seven.  
since the above distance agrees with the Official Field  
Notes of this section, making due allowance for the fraction  
on west side thereof I proceed thence,
- East
- 3941.5 To NW corner NE $\frac{1}{4}$  SE $\frac{1}{4}$  said section 7. which I establish  
with a basalt stone 8"x12"x10" set in the ground and  
chiseled  $1\frac{1}{16}$  C.S. thence,
- S. 89° 31' W. South
- 2653.0 To the south west corner of the south east quarter of  
the south east quarter of said section seven, which I  
establish with a basalt rock 6"x13"x7" set in mound  
of stone, chiseled  $1\frac{1}{16}$  C.S. thence,
- East
- 1344.0 To S.E. corner of section seven township thirteen south  
Range twenty six east of the Willamette meridian.

Date, surveyed, Dec, 3, 1920.

Date recorded Jan, 8, 1921.

Assistants sworn, L. Lynn George, Ralph Curl.

Survey by *Vernon L. Glaze* County Surveyor.

13-26