

Survey of Section 27, T 12 S, R 29 E, W M  
 Eastern Oregon Land Co.  
 January 28, 1934

Commencing at the SW corner of section 27, T 12 S, R 29 E, W. M.

Thence East on true line 1340.0 feet  
 Thence S 76 degrees 31' E. 270.0 " to dodge dense brush  
 Thence N 32 " 57' E. 680.0 " " " " "  
 Thence S 35 " 03' E. 200.0 " " " " "  
 Thence S 87 " 23' E. 90.0 " Which point is on true E - W line  
 Thence east on true line 76.0 " To fence corner. A 30" Yellow pine tree with old scribing is visible. Acceptable as witness for S 1/4 corner Sec. 27

The total easting of the above traverse notes is 2642.7 feet. From station 7 to about station 20 the present fence is south of true section line from 5.0 to 20.0 feet. Thus enclosing approximately 0.4 acre of section 34.

Commencing at the NW corner section 27, T 12 S, R 29 E, W. M. Thence easterly on random line 2648.0 feet. Witness to the N 1/4 corner of this section is plainly marked on a large Juniper tree about 75.0 feet north of said random line.

Set transit over point as nearly as could be ascertained from bearing tree where original 1/4 corner should be. Thence turned a true south course. Thence

South on true course 2640.0 feet Set stake in rock mound for center of section 27.  
 South on true course 5280.0 " Intersect south line of said sec. 27 about 3.0 feet west of the S 1/4 corner as recognized by witness tree mentioned above

March 18, 1934:

Commencing at middle of section 27, T 12 S, R 29 E, W. M. Thence East on true line 2649.0 feet. Intersect E 1/4 corner said section 27.

Thence South random line 2643.0 " To dodge dense brush and thickets. Intersect S line section 27, 125.0 feet west of SE corner. Corrected course for east line of the SE/4 said section 27.

L. E. Lucas  
 County Engineer.

Filed for record March 24, 1934