

Survey No. 7.

9-26

Made on application of John Burge and John Moucks Es Sections 2, 3, 11, and 12 Township 9 South Range 26 East D.M.

Commenced by qualifying on oath John Allen as Chainbearer, and carrying one end of chain myself.

Chs dist-
40.00
80.00

39.00
40.05
60.00
78.14
80.90

I run North on true course Bar $20^{\circ}45'E$ from section corner to sections 11, 12, 13 and 14 on section line between secs 11 and 12

find $\frac{1}{4}$ section cor
" section cor as indicated in notes being at stone $9 \times 8 \times 8$ ins in stone mound

Thence West on true course Bar $20^{\circ}E$ Ravine SE as indicated in field notes

find No corner as indicated in notes Ravine SE as indicated in notes

Run 140ms dia as indicated find sec cor to secs 2, 3, 10 and 11 in good condition

I then run East on same line and placed stone $3 \times 14 \times 18$ ins in stone mound $\frac{1}{4}$ from which Juniper tree 28 in in dia bears $N 42^{\circ}E$ 54 links dist-

done in presence of John Allen and John Burge
May 30th 1895

D. F. White
Co Surveyor

County of Grant
State of Oregon

I hereby Certify that I made the above survey and established the cor mentioned all courses and lines as to lengths and bearings being in accordance with ^{copy} original notes of U.S. Survey on file in my office

D. F. White
Co Surveyor

Recorded Sept-18th 1895