

Chas links

South face and CS on top from which yellow pine 48 ins dia bears S 24° W 5 links distant
Yellow pine 42 ins dia bears N 60 East - 3 links dist
Thence West bar 20° E

10.00

Placed granite stone 12 x 18 x 36 in mound of stone marked 1x and CS on of South face from which yellow pine 24 ins dia bears N 22° W 33 links distant -
Yellow pine 14 ins dia bears N 70° E 46 links distant
Thence South bar 20° E

3.50

Creek 5 links wide runs S 65° E

10.00

Set stake 4 in x 4 marked CS
Thence East

10.00

to corner on section line marked 16 CS
Then commenced at cor marked 16 CS and run East on True Course bar 18° E

5.00

Placed stone marked v on East face and CS on North face from which yellow pine 14 ins dia bears N 5° W 9 feet dist -
Thence N on True Course bar 18° E

5.00

Placed stone 8 x 10 x 14 ins resting on charcoal buried 1 foot deep. Marked CS and 11 from which tamarack 30 ins dia bears South 26° W 26 links dist - Thence W on T. C

5.00

Placed stone 8 x 12 x 14 and buried charcoal 1 foot deep. From which yellow pine 30 ins dia bears N 60° W 37 links dist and Tamarack 18 ins dia bears S on line 61 links dist.

This survey established all the corners of H Caldwell's Mining Claim, being SE 1/4 of NE 1/4 of SE 1/4 sec 31 and N 1/2 of S 1/4 of NW 1/4 of SW 1/4 of section 32, Township 10 South Range 35 East - Willamette Meridian Oregon containing 15 acres

Made this 3rd day of September 1895
W. White

County Surveyor

Recorded February 26th 1896