

Notes of Survey No 13

Made on application of R J Galbraith to establish lost 1/4 sec cor on Sec line bet secs 9 and 10 Township 13 South Range 33 East Gr. M. After duly qualifying on oath Clement Glasgow and acting myself as chainbearer and also as marker. I proceeded to make the following survey.

13-33

Commencing at sec cor to secs 4, 5, 8 and 9. Township 13 South Range 33 East Gr. M. Oregon, and running East on true course bar  $18^{\circ}30'$  East

40.15 chains find 1/4 sec cor in good condition and on line which is a stone  $15 \times 11 \times 6$  ins in stone mound as described in G. S. field notes

80.30 find no sec cor as indicated in G. S. field notes

81.02 " cor placed by Co Surveyor J Deal (no record)

I then commenced at 1/4 sec cor on N. bdy of sec 9 and run S bar  $18^{\circ}30'$  East

40.00 to centre of sec 9. and placed temp cor Thence East bar  $18^{\circ}30'$  East

40.24 placed temp 1/4 sec cor

I then commenced at sec cor to secs 9, 10, 15 & 16 and run N on bar  $18^{\circ}31' E$

40.00 to temp 1/4 sec cor which I find on line. Established permanent 1/4 sec cor by placing basalt stone  $6 \times 14 \times 20$  ins 6 ins in ground and buried broken glass 18 ins deep and digging pits on line, done in presence of R J Galbraith and Clement Glasgow

State of Oregon }  
County of Grant }<sup>ss</sup>

Same as in Book B page 5

I hereby certify that I made the foregoing survey and established corners as described

Dated this 19<sup>th</sup> day of September 1895

R J White Co Surveyor

Recorded Sept-21<sup>st</sup> 1895