

Notes of Survey No 13

13-33
 Made on application of Dr. J. Galbraith to establish lost 1/4 sec cor on Sec line bet- Secs 9th and 10th Township 13 South Range 33 East - Dr. M. After duly qualifying on oath Clement Glasgow and acting myself as chainbearer and also as marker. I proceeded to make the following survey

Commencing at sec cor to secs 4, 5, 8 and 9, Township 13 South Range 33 East - Dr. M., Oregon, and running East on true course var $18^{\circ} 30'$ East -
 Chains
 40.15 find 1/4 sec cor in good condition and on line which is a stone $15 \times 11 \times 6$ ins in stone mound as described in Dr. S. field notes
 80.30 find no sec cor as indicated in Dr. S. field notes
 81.02 " cor placed by Co Surveyor J. Deal (see record)
 I then commenced at 1/4 sec cor on N body of Sec 9 and run S var $18^{\circ} 30'$ East
 40.00 to centre of sec 9, and placed temp cor
 Thence East var $18^{\circ} 30'$ East
 40.00 placed temp 1/4 sec cor
 I then commenced at sec cor to secs 9, 10, 15 & and run North var $18^{\circ} 31' E$
 40.00 to temp 1/4 sec cor which I find on line
 Established permanent 1/4 sec cor by placing basalt stone $6 \times 14 \times 20$ ins 6 ins in ground and buried broken glass 18 ins deep and digging pits on line, done in presence of Dr. J. Galbraith and Clement Glasgow
 State of Oregon
 County of Grant }^{ss}

I hereby certify that I made the foregoing survey and established corners as above
 Dated this 19th day of September 1895

Dr. J. White - Co. Surveyor
 Recorded Sept-21st 1895