

Chas links

South face and CS on top from which yellow
pine 48 ins dia bears S 24° W 5 links distant
Yellow pine 42 ins dia bears N 60 East - 3 links dist
Thence West - Var 20° E

10.00

Placed granite stone 12 x 18 x 36 in mound of
stone marked 1X and CS on of South face
from which yellow pine 24 ins dia bears N 22° W
33 links distant -

Yellow pine 14 ins dia bears N 70° E 46 links dist
Thence South Var 20° E

3.50

Creek 5 links wide runs S 65° E

10.00

Set plate 4 in x 4 marked CS
Thence East

10.00

to corner on section line marked to CS
Then commenced at cor marked to CS and
run East on True Course Var 18° E

5.00

Placed stone marked V on East face and CS on
North face from which yellow pine 14 ins dia
bears N 5° W 9 feet dist -

Thence N on True Course Var 18° E

5.00

Placed stone 8 x 10 x 14 ins resting on char-
coal buried 1 foot deep. Marked CS and 11 from
which tamarack 30 ins dia bears South 26° W
26 links dist - Thence W on T. C

5.00

Placed stone 8 x 12 x 14 and buried charcoal 1 foot
deep. From which yellow pine 30 ins dia
bears N 60° W 37 links dist and Tamarack
18 ins dia bears S on line 61 links dist.

This survey established all the corners of H
Baldwells Mining Claim, being SE 1/4 of NE 1/4
of SE 1/4 sec 31 and N 1/2 of S 1/4 of SW 1/4 of SW 1/4
of section 32, Township 10 south Range 35 East
Willamette Meridian Oregon containing 15 acres

Made this 3rd day of September 1895

W. White

County Surveyor

Recorded February 26th 1896