

Notes of Survey No 14

Made on application of Dr. J. Galbraith, to establish corners.

After duly qualifying on oath Clement Lyman
and acting myself as chamberlain also as marker.
I proceeded to make the following survey:

Commencing at cor to secs 9, 10, 15 and 16 Township
13 South Range 33 East Willamette Meridian, Oregon
and running North on true course bar $18^{\circ} 30'$ East
on section line between sections 9 & 10

left bank of John Day River

Stake said to be placed by J. D. Pack for 16 corner

$\frac{1}{4}$ sec cor from which I run steel bar $18^{\circ} 30'$ East
to temp centre cor sec 9. which I established for
permanent cor. by placing stone 6 x 8 x 16 ins thick
C.M. S 9 (for centre permanent sec 9) on N face and
C.S. for County Surveyor on top. buried broken glass
18 ins deep beneath stone.

I then commenced at $\frac{1}{4}$ sec cor on sec line bet-secs 9
and 10 and run it $18^{\circ} 30'$ East

placed stone 6 x 10 x 14 . 6 ins in ground md to N face
and 6. 8 on S side in mound of stone from which
cottonwood tree dr of Dr J Galbraith's House bears
S $56^{\circ} E$ on Magnetic Course about 10 chains dist
I then run East from $\frac{1}{4}$ sec cor on line bet-secs 9 & 10
bar $18^{\circ} 30'$ East

Right bank of John Day River. Placed 3rd line cor which is
a stone 6 x 6 x 10 in stone mound N.M. S 10. C.S. I then run 2.07 chs
E on offset line thence 1.50 chs East to true line and find
fence on line bet land of Dr McHale & Dr J Galbraith
to be as near on line as practicable

State of Oregon
County of Grant). I hereby certify that I made the fore-
going Survey and established the corners as described
Dated this 19th day of September 1895

J. F. White Esq Surveyor

Recorded September 21st 1895

J. F. White Esq Surveyor