

# Notes of Survey No 14

Made on application of Dr. J. Galbraith, to establish corners.

After duly qualifying on oath Clement Glasgow and acting myself as chainbearer also as marker. I proceeded to make the following survey:

13-33  
Commencing at cor to secs 9, 10, 15 and 16 Township 13 South Range 33 East - Willamette Meridian Oregon and running North on true course bar  $18^{\circ} 30'$  East - on section line between sections 9 & 10  
chains  
8.50 left bank of John Day River  
20.00 stake said to be placed by J & Mack for  $\frac{1}{16}$  corner  
40.00  $\frac{1}{4}$  sec cor from which I run West bar  $18^{\circ} 30'$  East -  
40.24 to temp centre cor sec 9 which I established for permanent cor. by placing stone  $6 \times 8 \times 16$  in. <sup>in</sup> ~~in~~ C.M. S 9 (for centre government sec 9) on N face and C S for County Surveyor on Top. buried broken glass 18 in deep beneath stone.

I then commenced at  $\frac{1}{4}$  sec cor on sec line bet- secs 9 and 10 and run N  $18^{\circ} 30'$  East -

20.00 placed stone  $6 \times 10 \times 14$  6 in in ground mkd  $\frac{1}{16}$  on N face and C. S on S side in mound of stone from which Cottonwood tree N of Dr. J. Galbraith's house bears S  $56^{\circ}$  E on magnetic course about 10 chains dist.

I then run East from  $\frac{1}{4}$  sec cor on line bet- secs 9 & 10 bar  $18^{\circ} 30'$  East -

38.50 Right bank of John Day River. placed distance cor which a stone  $6 \times 6 \times 10$  in stone mound mkd C.M. S 10. C.S. I then run 2.00 chs N on offset line thence 1.50 chs East to true line and find fence on line bet- land of G & McHaley and Dr. J. Galbraith to be as near on line as practicable

State of Oregon }  
County of Grant }  
I hereby certify that - I made the foregoing survey and established the corners as described  
Dated this 19<sup>th</sup> day of September 1895

J. F. White Co Surveyor

Recorded September 21<sup>st</sup> 1895

J. F. White Co Surveyor