

Notice of Survey No. 15

In Sections 34^Q 35^Q 7^R 8^R 31^E.

Survey No. 15, made on application of Samuel Reynolds, for the purpose of restoring lost and obliterated corners, After duly qualifying on oath Clement Glasgow and Mat L. Jones as chainbearers, and acting myself as marker, I proceeded to make the following survey:

8-31

Commencing at corner of Sections 34, 35, 26 & 27, Township 8 South, Range 31 East Willamette Meridian, Oregon, ^Q running South on true course var-19^o

Chains.

East on section line between sections 34^Q & 35^Q

40.00

Find no 1/4 section corner.

82.22

Find Standard corner to sections 34^Q & 35^Q to be destroyed, Stone mound still remaining.

I then went to Standard cor. to 35^Q & 36^Q and run West var 17^o East

80.00

Find Stone mound to be true corner which I established by placing stone 10' x 12' x 16' marked with two notches on East 4 on West and 6 on North face, and built stone mound around.

I then run North var 19^o East

40.00

Find 1/4 Section stone rolled down hill ten feet? established it on line and built stone mound around.

80.00

Find stone mound that I commenced at to be not the true corner and bearing no marks.

I then went to cor. to Secs. 22, 23, 26^Q & 27 and run S, var 19^o E

80.00

Establish for corner stone 12' x 14' x 20' in Stone mound All said corners established in presence of Samuel Reynolds, Mat L. Jones & C. Glasgow,

State of Oregon } ss.
County of Grant }

I hereby certify that I made the foregoing survey and established the corners as described,

Dated this 2nd day of October 1895,

W P White

County Surveyor

Reed for Record Oct 5th 1895