

Notice of Survey No. 15

In Sections 34<sup>q</sup> 35<sup>q</sup> 788R318.

Survey No 15, made on application of Samuel Reynolds.  
for the purpose of restoring lost and obliterated corners,  
After duly qualifying on oath Clement Glasgow and  
Mat L. Jones as chainbearers, and acting myself as  
marker, I proceeded to make the following survey:

Commencing at corner of Sections 34, 35, 26 & 27, Township 8 South, Range 31  
East Willamette Meridian, Oregon,  $\frac{1}{4}$  running South on true course var  $19^{\circ}$

Chains.

40.00

82.22

80.00

40.00

80.00

80.00

East on section line between sections 34<sup>q</sup> & 35<sup>q</sup>

Find no  $\frac{1}{4}$  section corner

Find Standard corner to sections 34<sup>q</sup> & 35<sup>q</sup> to be  
destroyed, Stone mound still remaining.

I then went to Standard cor. to 35<sup>q</sup> & 36 and run West var  $19^{\circ}$  East

Find Stone mound to be true corner which I established by  
placing Stone 10 X 12 X 16 marked with two notches on East  
4 on West and 6 on North face, and built stone mound  
around.

I then run North var  $19^{\circ}$  East

Find  $\frac{1}{4}$  Section stone rolled down hill ten feet, established  
it on line and built stone mound around.

Find stone mound that I commenced at to be not the  
true corner and bearing no marks.

I then went to cor. to Secs. 22, 23, 26 & 27 and run S var  $19^{\circ}$  E

Establish for corner stone 12 X 14 X 20 in Stone mound

All said corners established in presence of Samuel  
Reynolds, Mat L. Jones & C. Glasgow,

State of Oregon } ss.  
County of Grant }

I hereby certify that I made  
the foregoing survey and established the corners  
as described,

Dated this 2<sup>nd</sup> day of October 1895.

W P White

County Surveyor

Reed for Record Oct 5<sup>th</sup> 1895