

Survey No 17 application of balance
In Township 10 South Range 26 East
Willamette Meridian Oregon

10-26

After qualifying on oath of Templeton
and J M Templeton as Chain carriers and acting
myself as marker.

I commenced at 1/4 sec cor on sec line
between secs 6 and 7 Tp 10 S. R 26 East and
run west on true course bar 19° 30' East
To right bank of South Fork of John Days
River. I placed flag on opposite side of river and
on line. I then run 50 links S for base. find flag
on opposite bank bears N 73° 30' West which gives for
distance across river, 169 links, which added to 13.76
makes to left bank of river

Chs links
13.76

14.45
20.00

Placed stone 6 x 12 x 8 marked to CS in stone mound
Thence I run South bar 19° 30' E

20.00

placed stone 6 x 14 x 16 ins inked to CS raised stone mound
around corner. left flag on corner for proof line.
I again commenced at 1/4 sec cor on sec line
bet secs 6 and 7 and run N bar 19° 30' E

20.00

placed fir post 6 ins on three sides (triangular post)
in mud swamp marked to CS.
Thence again from 1/4 sec cor on line bet 6 and 7 and
run South bar 19° 30' E

20.00

Placed stone 6 x 8 x 16 in, stone mound marked to CS
from which flag left on corner on opposite side of river
bears West on bar 19° 30' E

Dec 16th 1895

Commenced at 1/4 sec cor on sec line bet
secs 6 and 7 and run East bar 19° 30' E
find cor to secs 5, 6, 7 and 8 in good condition
I then run west on same line

42.80

21.40

Placed stone 6 x 10 x 16 in stone mound for 1/4 cor
Thence North bar 19° 30' E on random line

70.00

placed temporary corner.