

Survey No 20

In Twp 9 South Range 28 East
on Application of G & S. Haley

9-23

Commenced at cor to Secs 26, 27, 34, ^{and} 35
(See Book B Bearing Trees Government Survey)
and run North on true line bearing $20^{\circ}30' E$

20.00 establish to cor stone 6 x 10 x 14 ins set
to cs in stone mound for SW cor of NW 1/4 sec 26

40.00 to established cor

60.00 set stone 3 x 14 x 16

80.00 section cor 22, 23, 26 ^{and} 27
Thence East $20^{\circ}30' E$

20.00 set stone 6 x 8 x 12 ins set to cs in mound of stone
for S.W. cor of E 1/2 of SW 1/4 sec 23

40.00 to established 1/4 sec cor on line bet 23 and 26
I then run North bearing $20^{\circ} E$

40.00 set stone 12 x 10 x 16 centre of sec 23
Thence ~~W~~ ^N $20^{\circ}30' E$

20.00 set stone 8 x 12 x 4 in stone mound for ^{SW} cor to
to East 1/2 of S 1/4 sec 23

Thence from 1/4 sec cor on line bet-sec
23 and 26. I run East bearing $20^{\circ} E$

20.00 set stone 9 x 10 x 28 in stone mound set to cs
for NE cor to NW 1/4 of NE 1/4 sec 26
thence South bearing $20^{\circ} E$

20.00 stone 10 x 14 x 18 in stone mound set to cs

I then commenced at SW cor of NW 1/4 of SW 1/4
sec 26 and run East bearing $22^{\circ} E$

20.00 set stone 6 x 12 x 14 set to cs in stone mound, thence $N^{20^{\circ} E}$

20.00 stone 12 x 10 x 16 set to cs thence E bearing $24^{\circ} E$ and

20.00 stone 8 x 12 x 4 set to cs thence $N^{22^{\circ} E}$

20.00 to SW cor of NW 1/4 of NE 1/4 sec 26 and closing there (at

Feb 7th 1896

W. White

Recorded Feb 26th 1896

County Surveyor