

14-29

Survey No 23. Made on Application of Minerva A. Reeves. to retrace section line between sections 4 and 5 and establish lines and corners of lot-4 in section 4 and lot-1 in section 5 Township 14 South Range 29 East D.M.

After qualifying on oath John A Shelly and James A Popel as chainbearers

Commenced at corner to sections 4 and 5 on North boundary of Township. which is a grey stone 6x8x12 inches in a mound of stone and marked 6 notches on South face. 2 notches on West-face and 4 notches on East-face and run South on standard line at a bearing of 20° E

Chain dist
8.50
10.00
13.00
14.30

E
3.00
7.50

9.50
20.00

Creek runs East
Fence " E and Dr enter field
leave field fence N E and S W
Find 44 section cor in good condition
Then run East from 44 section cor by bear 20° E found by backlight on course

Enter field
Creek runs N W placed stone 10x12x24 ins in stone mound marked W and CS on West-face for witness corner also S.W. of lot-4 sec 4 and run N. on offset-line bear by backlight- 19° 30'. 2 chains East on offset-line bear 19° 30' 2 chains N on offset-line bear 19° 30' 2 chains to fence and creek " " " " 7.30 to point on

Township line 9.50 chains East of sec cor described as commencing point - Thence E on sec line 10.50 chain placed stone 12x20x26 in stone mound marked W and CS on East-face for N E cor of lot-4. sec 4 Township 14 South Range 29 East
Made March 11th 1896

W. White
County Surveyor

Recorded April 16th 1896