

Survey No 28

Made on application of R A Thomas to subdivide sec 17
T₁₀ S R 23 East

20-23

After duly qualifying on oath R R Keys and Hugh
Wilson as Chainbearers, and acting myself as marker.
I proceeded to make the following survey:
Commencing at 1/4 sec cor on line bet- secs 16 and 17
Township 10 South Range 23 East - Gilliamette Jurisdiction
Oregon, and running South on true course bearing 21° East
on section line between secs 16 and 17
40 chain find intersection of blazed line and stone mound,
corner destroyed, established cor by placing stone
12 x 12 x 12 marked 3 notches on S face 2 notches on E face
4 notches on West face and 3 notches on N face and placed
stone mound around corner in presence of R R Keys and
Hugh Wilson.

Chs links
85.75

42.87

I then run West bearing 21° 30' East on line bet- secs 17 and 18
at 40 chain and 70 links find stone in mound marked 1/4
intersect N and S line 5 chain N of sec cor to secs 17, 18,
and 20. I then run East on true line bearing 25° 30' E
placed stone 6 x 12 x 16 marked 1/4 on S face and CS on
base in presence of R R Keys and Hugh Wilson.

41.40

I then commenced at cor to secs 8, 9, 17 and 16 T₁₀ S.
R 23 E and run W on true line bet- 8 and 17 bearing 20° 30' E
find stone marked 1/4 S. size and description agreeing
with original notes at 40 chain

87.17

43.38

intersect N and S line 5 chain N of cor to secs 7, 8, 17 and 18
I then run E bearing 25° 30' E 43.38 chain and placed basalt
stone 4 x 12 x 16 marked 1/4 and CS on W face in presence
of R R Keys and Hugh Wilson. From which corner I
run a line through centre of sec 17 to corresponding 1/4 cor
on S boundary of sec 17 and also ranged line from 1/4 cor
on W bdy to 1/4 cor on E bdy and at intersection of lines
placed basalt stone 24 x 12 x 9 ins marked C17 and C18
in mound of stone

Made 31 day of March 1896

J F White - County Surveyor