


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

INDEX No. A-1

**History of original corner establishment:**

Corner was originally established by W.H. Byars, in June, 1873, under General Land Office Contract No. 185. U.S. Surveyor Generals Notes State: Set corner to Townships 10 & 11 South, ranges 28 & 29 East. A Stone 18x14x12.



In 1879 E.A. Thatcher, under General Land Office Contract No. 325 made the original survey of the Line between T10 & 11 S., R28E., He intersected the Range Line 50 lks North of the corner as established by Byars and Set a Corner at that position. In Sept. 1880, under General Land Office Contract No. 371. Aaron F. York, Retraced the line to T.11S., R.28/29E., U.S. Surveyor Generals Notes State: I found Stone 20x14x12 for cor. to Townships 10 & 11 S. R.28 & 29 E. I raised Stone mound at Cor.

**Description of corner evidence found:**

Found 20"x16"x14" stone, with 6 notches on three edges, loose in a mound of stone.

There are no accessories originally established. Accepted a hole in the center of the above described mound of stone as the corner position.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 16" in the ground, set the original stone North alongside pipe and raised a mound of stone & earth around pipe.

From Which:

- A Juniper 5" dia., Bears S81°W., 5.9 ft., scribed: T11S R28E S1 BT
  - A Juniper 10" dia., Bears N61°E., 32.3 ft., scribed: T10S R29E S31 BT
  - A Juniper 11" dia., Bears S68°E., 16.6 ft., scribed: T11S R29E S6 BT
- Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East. Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Sign, North 4 ft. from the corner.

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

**OREGON**  
JULY 12, 1859  
**DOUGLAS M. FERGUSON**  
**848**

This work is performed by:  
Douglas M. Ferguson RLS 848  
Mt. Vernon Oregon.  
On: Nov. 25, 1986  
Refer to Map of Survey No. 965

Office of..... Surveyor ..... County of..... Grant .....  
State of..... Ore gon ....., I hereby certify that the within instrument was filed in this office  
for record on the 18 day of..... April ....., 1987  
..... Robert D. Bayett by .....  
(COUNTY OFFICIAL) (DEPUTY)