


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Not previously established



Description of corner evidence found:

A blazed line runs south and west from corner location. These lines were evidently run by Bert Udell (no date) as noted on location tags set at other points.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the established corner location I set a standard F.S. aluminum monument consisting of a 3" disk mounted on a 2 1/2 x 30" pipe with a 4 x 4 1/2" footplate buried 20" in the ground with 10" protruding above the ground and surrounded by a rock mound 10" high by 3 feet in diameter. Disk is stamped as shown.



Witnesses: P. Zabala and S. Moss

New BT's established :-

- a 15" P. Pine bears N. 68°17' E., 55.3 ft. distant, scribed N 1/16, S. 27, BT
- a 10" P. Pine bears S. 36°16' W., 21.7 ft. distant scribed N 1/16, S. 28, BT

Both are banded with red paint, carry BT and Attention signs and have brass disks stamped PLS 1287 nailed to the base of the BT blaze.

Steel fence posts with boundary signs lie 3 feet west and 3 feet south of corner monument



Office of... *Surveyor* ... County of... *Grant* ...
State of... *Oregon* ... I hereby certify that the within instrument was filed in this office
for record on the... *23* day of... *Nov* ... 19... *82* ...
by... *Robert D. Bayliff* ...
(COUNTY OFFICIAL) (DEPUTY)