

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

F-5

History of original corner establishment:

None

DIAGRAM

T7S R26E
N 1/16
S7 S8

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

Set 32" X 2" flanged iron pipe with brass cap marked:

T7S R26E
N 1/16
S7/S8
1979
PLS 346

Ponderosa Pine, 10" Dia., BRS. S27 $\frac{1}{2}$ ^OE, 64.6 Ft. Distance

Marked: N1/16 S8 BT

Ponderosa Pine, 12" Dia., BRS. N77 $\frac{1}{2}$ ^OW, 38.5 Ft. Distance

Marked: N1/16 S7 BT

6' Iron Fence Post with "Survey Monument" sign within 5' of Corner.

All BTs have BT tag, painted red stripe and brass washer stamped: PLS 346; nailed to lower blaze.

Office of.....County Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 4 day of Oct 1979
Robert D. Gayden by
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
MAY 6, 1955
WAYNE O. HARRIS
346