

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J - 9 DIAGRAM

History of original corner establishment:

The original corner was established by Frank W. Campbell on May 13, 1881, under GLO contract No. 380, as follows:

Set a basalt stone, 24" x 15" x 15", and dug pits for cor. to sec's 8, 9, 16 & 17.

T7S R29E
S8/S9
S17/S16
PLS 1636
2001

Corner evidence recovered:

At a position harmonious with recovered original corners to the north and east, I found a very large mound of stones. I carefully inspected every stone in the mound (none which are as large as record) and found none with marks. This area is flat farm land, and there are no other stones in the vicinity. I accept this mound of perhaps 100 stones as an unrecorded perpetuation of the original corner point.

Monument and accessories established to perpetuate the original position of this corner:

In the center of the recovered stone mound, which point is about 3 feet south of an east - west fence line, I set a 1" x 30" flared, galvanized iron pipe 18" into the ground. A 2 1/2" brass cap attached to the top of the pipe is marked as shown in the diagram above. I build a mound of stones around the pipe, from which:

A 5/8" x 36" iron rod, set 35" into the ground with a 3/4" brass washer, marked "PLS 1636 S9", attached at ground level, bears N88° E, 67.9 feet.

A 5/8" x 30" iron rod, set with the top one foot below the ground surface with a 3/4" brass washer, marked "PLS 1636 S16", attached 1" below the top of the rod, bears S25° E, 102.5 feet.

A 5/8" x 30" iron rod, set with the top one foot below the ground surface with a 3/4" brass washer, marked "PLS 1636 S17", attached 1" below the top of the rod, bears S33° 30' W, 113.3 feet.


A 5/8" x 36" iron rod, set 35" into the ground with a 3/4" brass washer, marked "PLS 1636 S8", attached at ground level, bears N87° 30' W, 93.6 feet.

I hereby certify the above corner point was perpetuated as hereon described on July 10, 2001. Magnetic declination set in compass: 18° E.

RECEIVED AND
FILED

July 24, 2001

OFFICE OF COUNTY SURVEYOR
Robert A. Beyer
Attest: Michael S. Beyer



Renews June 30, 2003

Recorded at the office of County Surveyor, County of Grant, State of Oregon, on _____, 2001