CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Not established during original survey.

DIAGRAM

W $\frac{1}{16}$ $\frac{31}{6}$ T6S T7S R31E

Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

Monument Established

At the corner point as determined by survey and proportionate measurement between the N 1/4 corner and the NW corner of Section 6, T7S, R31E, we set a 2"x30" Galvanized Iron Pipe, 16" in the ground and supported in a mound of stone 4 ft. dia. base to top of pipe, with brass cap attached, marked:

T6S
S31 R
W $\frac{1}{16}$ 31
S6 E
T7S
PLS 1099
1982

From which we mark the following BT's:

A 17" Ponderosa Pine, scribed "W 1/16 S31 BT" on a double blaze bears N 71½°W 33.0 ft.

And a 22" Ponderosa Pine, scribed "W 1/16 S6 BT" on a double blaze bears S13½°W 32.2 ft.

Attached brass washer marked "LS 1099" to lower blaze of new BT's.

Corner location established and perpetuated in accordance with Umatilla National Forest Cadastral Survey Contract No. 53-04R3-2-01275.

Magnetic Compass (18½° East Declination)

Witnesses: Greg Orton
Jeff Anderson

August 26, 1982

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 22, 1977
GARY L. LANGLITZ
1099

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 25 *day of* Jan, *19* 83
Robert D. Leggett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

A-2