CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original survey by Meldrum and Campbell, Contract 380, 1881;

Set a basalt stone 14x12x10 in a mound of stone for 1/4 sec. cor.

DIAGRAM

T7S
1/4
R30E 1 | 6 R31E

Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

Corner location determined by survey and single proportionate measurement between the NW corner of Sec. 6 and the SW corner of Sec. 7, T7S, R31E.

At the corner point, we set a 2" dia. bronze disk cemented in a crevice of a bedrock outcrop, approx. 1½ ft. above ground (outcrop dimensions 3'x3'x1½' high), marked:

T7S
1/4
R 30 E S1 | S6 R 31 E

PLS 1099
1982

From which we mark new BT's:

A 14" Juniper, scribed "1/4 S6 BT" on a double blaze bears S69°E 67.4 ft.

And a 12" Juniper, scribed "1/4 S1 BT" on a double blaze bears S69°W 96.6 ft.

Attached brass washer, marked "LS 1099" to lower blaze of new BT's.

Corner location monumented and perpetuated in accordance with our survey contract.

Magnetic Compass (Declination 18½° East)
Steel Tape.

Witnesses: Gary Langlitz
Greg Orton
Jeff Anderson

September 2, 1982

REGISTERED PROFESSIONAL LAND SURVEYOR
Gary L. Langlitz
OREGON
JULY 22, 1977
GARY L. LANGLITZ
1099

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 25 day of Jan, 19 83
Robert D Bagett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

C-1