


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Forest W. Campbell under G.L.O.
 Contract No. 380. Surveyor General records state:
 Set Basalt stone 18"x18"x12" in a mound of stone.



Description of corner evidence found:


Ring of stone with a stone 18"x17"x11" in the center, no chisle marks, fits calls to creek and ridge top to South and East.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2½" Brass Cap on 2½" x 30" Gal. steel pipe marked as shown 5" in ground, hit hard pan, built mound of stone around monument and original stone.

From which:

- 16" Pine bears N62°E, 168.8 ft. scribed T7SR31ES10 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
 - 14" Pine bears S27°E, 126.4 ft. scribed T7SR31ES15 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
 - 8" Pine bears S40°W, 22.6 ft. scribed T7SR31ES16 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
 - 12" Juniper bears N20°W, 225.1 ft. scribed T7SR31ES9 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
- Set steel guard post with signs 54-4 and 54-2 6 ft. South.
 Posted signs 54-4 and 54-3 on BT's.
 Painted red band around BT's and painted blazes red.



**REGISTERED
 PROFESSIONAL
 LAND SURVEYOR**

Larry D. Bishop
**OREGON
 JULY 17, 1980
 LARRY D. BISHOP
 896**

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within Instrument was filed in this office
 for record on the 31 day of Dec 1980
Robert D. Bayett by _____
 (COUNTY OFFICIAL) (DEPUTY)