


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1881 by Henry Meldrum under General Land Office Contract No. 380.

Surveyor General Records (Notes) states:  
Set a basalt stone 18x8x8 in. in a mound of stone for cor. to secs. 13, 18, 19, 24 from which a pine 9 in. in dia. bears S88°E 57 lks.



(No subsequent remonumentations found in county records)

Description of corner evidence found:

Found a mound of stone and a bearing tree, 24 in. pine, live in good condition, with scribing visible, bearing S88°E 37.6 ft. from the center of the mound of stone.

Accepted the center of the stone mound as the corner position.

Description of monument and accessories established to perpetuate the original location of this corner

Set 30 in. x 2 1/2 in. iron pipe with 3 in. brass cap marked as shown 16 in. in the ground and raised a mound of stone around the pipe for the corner to Sections 13, 18, 24 and 19.

From which new BT's


- A pine 10 in. diam. bears N64°E 68.5 ft. dist. marked T7S R31E S18 BT.
- A pine 32 in. diam. bears S55°W 58.9 ft. dist. marked T7S R30E S24 BT.
- A pine 20 in. diam. bears N54°W 29.5 ft. dist. marked T7S R30E S13 BT.

Distances taken to a brass washer in the blaze of each tree. Set a steel fence post approximately 5 ft. south from corner with Forest Boundary sign attached.

Used steel tape and magnetic compass with declination = 20° E.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Douglas M. Ferguson*  
OREGON  
JULY 12, 1968  
DOUGLAS M. FERGUSON  
848



Office of County Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 16 day of Nov., 1972, at 1 o'clock Pm., (signed)  
*Douglas M. Ferguson* by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

SEE REMON FILED April '86