


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner first established by Henry Meldrum in 1881, under contract No. 380, dated March 19, 1881. He set a basalt stone 16" X 8" X 6", from which a Pine 24" dia. bears N.22°W. 69 lks., and a Pine 24" dia. bears n.12°E., 90 lks.



In 1974 Leland Myees remonumented the Corner setting 2 1/2" brass cap in a 2" X 30" galvanized iron pipe. Raissd stone mound 1' high and 3' in diameter around monument.



Description of corner evidence found:

2 1/2" diam. brass cap on a 2" iron pipe extending 6"± above ground. Cap mkd. per sketch.

- 28" D.B.H. (24") Ponderosa Pine, N.22°W., 69 lks. Dead and down.
- 28" D.B.H. (24") Ponderosa Pine, N.12°E., 90 lks., scribes on an open face. Lightning struck and dead.
- 4" x 4" wood post, w/ 54-2 & 54-4 signs attached, North, 3.8'.

Description of monument and accessories established to perpetuate the original location of this corner:

11" D.B.H. Ponderosa Pine, S.73°W., 25.9', scribed 1/4S24BT.
15" D.B.H. Douglas Fir, S.18°E., 15.0', scribed 1/4S19BT.
Set a brass washer mkd. RPLS 1910 between B&T on each B.T., painted bands and faces red, set B.T. tags and attn. signs. Also painted bands and faces red on other B.T.'s..
Distances are measured to center of tree 1' above the root crown. Bearings are Magnetic North, 20° East declination.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Clayton J. Martin

OREGON
JULY 18, 1980
CLAYTON-JESSE MARTIN
1910

C.J. MARTIN SURVEYING
2751 JUNIPER ST.
SWEET HOME, OR 97386

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 19 day of April, 1986
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)