


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Forest W. Campbell under G.L.O.
Contract No. 380. Surveyor General records state:
Set Basalt stone 17"x10"x8" in mound of stone.
From which:
An 18" Pine bears N75°E 119 lks.



Description of corner evidence found:


Orig. 18" now 30" Pine scribing visible N85°E, 84.0 ft. (record N75°E 78.5 ft.) of a stone 17"x10"x8" in a mound of stone, no marks visible.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2 1/2" Brass Cap on 2 1/2" x 30" Gal. steel pipe marked as shown 6" in ground, built mound of stone around monument.

From which:

14" Pine bears S30°W, 9.0 ft. scribed 1/4 S29 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
Set steel post with signs 54-4 and 54-2 3 ft. South.
Steel post with sign 54-2 3 ft. North.
Posted signs 54-4 and 54-3 on BT's.
Painted red band around BT's and painted blazes red.



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Larry D. Bishop

OREGON
JULY 11, 1909
LARRY D. BISHOP
896

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 31 day of Dec 1980
Robert D. Bayart by _____
(COUNTY OFFICIAL) (DEPUTY)