

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-17

History of original corner establishment:

Corner was set by Frank W. Campbell in 1883 under Contract No. 468, dated April 12, 1883.

Set a basalt stone, 16" X 10" X 10", 10" in the ground, marked with 2 notches on East and 4 notches on West edges.

DIAGRAM

T6S	R34E
S34	S35
S3	S2
T7S	

- A Pine, 30" diam., brs. N.79°E., 156 lks., marked T6SR34ES35BT.
- A Pine, 18" diam., brs. S.79°E., 126 lks., marked T7SR34ES2BT.
- A Pine, 30" diam., brs. S.63°W., 157 lks., marked T7SR34ES3BT.
- A Pine, 36" diam., brs. N.68°W., 189 lks., marked T6SR34ES34BT.

Description of corner evidence found:

No trace of stone.

- 28" D.B.H. (30") Ponderosa Pine (snag), N.83½°E., (N.79°E.), 107.3' (102.96') with scribes T6SR34ES25BT. Should be S35.
- 26" D.B.H. (18") Ponderosa Pine, S.82°E., (S.79°E.) 126 lks., face down, down snag.
- 39" D.B.H. (30") Ponderosa Pine, S.63°W., 157 lks., with scribes ES3 visible on a partially open blaze. Live tree.
- 36" D.B.H. Ponderosa Pine, down snag, N.65°W. (N.68°W.), 189 lks., scribed T6SR34ES34.

Stone mound, origin unknown, bears N.80° 19'E., 71.5', from Corner, true bearing.

Description of monument and accessories established to perpetuate the

original location of this corner:

Set at record distances from all but N.E. B.T., A 2½" diam. Alum. cap on a 2½" X 30" alum. pipe. Raised stone mound. Cap marked per sketch. Set steel posts 4'± East & West with attn. and mon. signs attached.


T6S	R34E
S34	S35
S3	S2
T7S	
RPLS 1910	
1985	

- 6" D.B.H. Ponderosa Pine, N.33°E., 17.1', scribed T6SR34ES35BT.
- 8" D.B.H. Douglas Fir, S.89°E., 73.7', scribed T7SR34ES2BT.
- 10" D.B.H. Douglas Fir, N.43°W., 65.7', scribed T6SR34ES34BT.

Set a brass washer marked RPLS 1910 between B&T on each B.T., set B.T. tags, attn. signs, painted bands and faces red.


Distances to B.T.'s. are to center of tree 1 foot above the root crown.

Bearings are magnetic with 20° East declination, except as noted.



Clayton J. Martin

C.J. MARTIN SURVEYING
2751 JUNIPER ST.
SWEET HOME, OR 97386



Office of Surveyor County of Grant
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 16 day of DEC, 1985
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)