


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-13

History of original corner establishment:

STONE 18X13X6 IN MOUND

AARON F. YORK, CONTRACT #309, Nov. 18, 1878



Description of corner evidence found:

Stone 18 X 13 X 6 in mound

BTs not of record

Ponderosa Pine, 18" Dia., BRS. S31°E, 8.8 Ft. Distance with scribing visible on open blaze.

Ponderosa Pine, 21" Dia., BRS. S76 3/4°W, 14.9 Ft. Distance with scribing visible on open blaze.

Description of monument and accessories established to perpetuate the original location of this corner

Set 32" X 2" flanged iron pipe with brass cap marked:

T6S R26E  
S4 | S3  
T7S R26E  
1979  
PLS 346

Ponderosa Pine, 8" Dia., BRS. S21°E, 22.6 Ft. Distance.

Marked: T7S R26E S3 BT

Ponderosa Pine, 8" Dia., BRS. S27 1/2°W, 29.0 Ft. Distance.

Marked: T7S R26E S4 BT

6' Iron Fence Post with "Attention" sign within 5' of Corner.

New BTS have BT tag, painted red stripe, and brass washer stamped: PLS 346; nailed to lower blaze.

Buried original stone along side iron pipe.

Office of County Surveyor County of Grant  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 4 day of Oct 1979.  
Robert D. Begett by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Wayne O. Harris*  
 OREGON  
 MAY 6, 1955  
 WAYNE O. HARRIS  
 346