

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


Refer to: Plat of Wilson 1985 Cadastral Survey
Sections 2&3, T.7S., R.26E., W.M.

C-17

History of original corner establishment:

Aaron F. York, under G.L.O. contract number 309,
dated Nov. 18, 1878, set a stone 9"X 9"X 7", from
which:

A Red Fir, 24" dia., N68°E, 20 lks.
A Tamarack, 20" dia., S70°W, 13 lks.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the
original location of this corner:

At proportionate distance I set a 2½"X 30" alum. pipe with a 3" alum.
cap containing a magnet and marked:

From which:

A Douglas Fir, 23" dia., N7¼°E, 11.3 ft.; marked: ¼ S2 BT
A White Fir, 14" dia., N60°W, 27.5 ft.; marked: ¼ S3 BT

T7S R26E
¼
S3 | S2
PLS 1832
1985

BTs have blaze and 6" stripe painted red, a BT tag, an "Attention"
sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze.
There is a 6' steel fence post with an "Attention" sign within 5'
of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic
declination set at 18½°E.

October 10, 1985

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro

OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832

Office of Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 10 day of Jan, 1985
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)