


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-5

History of original corner establishment:



STONE 18X10X8 IN MOUND

22" YELLOW PINE S70°W 47LKS

AARON F YORK, CONTRACT #309, Nov. 18, 1878

Description of corner evidence found:

Stone 18 X 11 X 9 in mound.

Description of monument and accessories established to perpetuate the original location of this corner

Set 32" X 2" flanged iron pipe with brass cap marked:

Douglas Fir, 10" Dia., BRS. N35 3/4°W, 49.5 Ft. Distance.

Marked: T7S R26E S6 BT

Douglas Fir, 13" Dia., BRS. N64 1/4°E, 47.8 Ft. Distance.

Marked: T7S R26E S5 BT

Ponderosa Pine, 10" Dia., BRS. S65 3/4°E, 59.0 Ft. Distance.

Marked: T7S R26E S8 BT

Ponderosa Pine, 10" Dia., BRS. S51 1/2°W, 62.4 Ft. Distance.

Marked: T7S R26E S7 BT

6' Iron Fence Post with "Attention" sign within 5' of Corner.

All BTs have BT tag, painted red stripe and brass washer stamped: PLS 346; nailed to lower blaze.

Buried original stone along side iron pipe.

T7S R26E
S6 | S5
S7 | S8
 1979
 PLS 346

Office of County Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 4 day of Oct 1979
Robert W. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Wayne O. Harris
 OREGON
 MAY 6, 1953
 WAYNE O. HARRIS
 346