


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-7

History of original corner establishment:

STONE 19x13x5 IN MOUND
 YELLOW PINE 24" N45°W 100LKS
 YELLOW PINE 22" S70°W 47LKS

AARON F. YORK, CONTRACT #309 NOV 18, 1878



Description of corner evidence found:

Stone 19 X 12 X 5 in mound.

Ponderosa Pine Snag, 19" Dia., BRS. S62°W (Record S70°W), 31.8 Ft. Distance (Record 47 Lks.) with scribing visible on open blaze.

Rotted Pine Stump, Approximately 2.5' Dia., BRS. N48 $\frac{1}{4}$ °W (Record N45°W), 68.2 Ft. Distance (Record 100 Lks.) with no scribing remaining.

Description of monument and accessories established to perpetuate the original location of this corner

Set 32" X 2" flanged iron pipe with brass cap marked:

Ponderosa Pine, 10" Dia., BRS. S29 $\frac{1}{2}$ °E, 21.3 Ft. Distance.

Marked: $\frac{1}{4}$ S 5 BT

Ponderosa Pine, 9" Dia., BRS. S32°W, 66.6 Ft. Distance.

Marked: $\frac{1}{4}$ S 8 BT

6' Iron Fence Post with "Attention" sign within 5' of Corner.

T7S R26E
 $\frac{1}{4}$ $\frac{S5}{S8}$
 1979
 PLS 346

All BTs have BT tag and painted red stripe; new BTs have brass washer stamped: PLS 346; nailed to lower blaze.

Buried original stone along side iron pipe.

Office of _____ County Surveyor _____ County of Grant
 State of Oregon _____, I hereby certify that the within Instrument was filed in this office
 for record on the 4 day of Oct 1979
 Robert D. Begett by _____
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Wayne O. Harris
 OREGON
 MAY 6, 1955
 WAYNE O. HARRIS
 346