


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-9

History of original corner establishment:

STONE 14x10x8 IN MOUND
TAMARACK 24" DIA. N85°E 8LKS
AARON F. YORK APRIL 4, 1879 CONTRACT #309



Description of corner evidence found:

Stone 18 X 10 X 6 in mound.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 32" X 2" flanged iron pipe with brass cap marked:

White Fir, 7" Dia., BRS. N21°W, 11.2 Ft. Distance.
 Marked: T7S R26E S5 BT
 White Fir, 12" Dia., BRS. N75¹/₄°E, 47.1 Ft. Distance.
 Marked: T7S R26E S4 BT
 White Fir, 8" Dia., BRS. S30°E, 19.1 Ft. Distance.
 Marked T7S R26E S9 BT
 White Fir, 9" Dia., BRS. S60¹/₂°W, 18.2 Ft. Distance.
 Marked: T7S R26E S8 BT
 6' Iron Fence Post with "Attention" sign within 5' of Corner.

T7S R26E
 S5 | S4
 S8 | S9
 1979
 PLS 346

All BTs have BT tag, painted red stripe and brass washer stamped: PLS 346; nailed to lower blaze.

Buried original stone along side iron pipe.

Office of County Surveyor County of Grant
 State of Oregon I hereby certify that the within instrument was filed in this office
 for record on the 4 day of Oct 1979
 Robert W. Bagitt by
 (COUNTY OFFICIAL) (DEPUTY)

