


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-13

History of original corner establishment:



STONE 18X14X8 IN MOUND

- 6" TAMARACK N70°W 8LKS
- 4" TAMARACK N25°E 8LKS
- 5" FIR S15°W 25LKS
- 4" FIR S40°E 10LKS

AARON F. YORK, CONTRACT #309, Nov. 18, 1878

Description of corner evidence found:

Stone 16 X 11 X 6

Tamarack, 18" Dia., BRS. N71½°W (Record N70°W), 5.3 Ft. Distance (Record 8 Lks.) with healed over blaze.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 32" X 2" flanged iron pipe with brass cap marked:

Douglas Fir, 17" Dia., BRS. N70¼°E, 4.9 Ft. Distance.

Marked: T7S R26E S 3 BT

White Fir, 10" Dia., BRS. S29 °E, 12.8 Ft. Distance.

Marked: T7S R26E S10 BT

White Fir, 9" Dia., BRS. S38 °W, 32.8 Ft. Distance.

Marked: T7S R26E S 9 BT

6' Iron Fence Post with "Attention" sign within 5' of Corner.

T7S R26E
S4 | S3
S9 | S10
 1979
 PLS 346

All BTs have BT tag and painted red stripe; new BTs have brass washer stamped: PLS 346; Nailed to lower blaze.

Buried original stone along side iron pipe.

Office of _____ County Surveyor _____ County of Grant _____
 State of Oregon _____, I hereby certify that the within instrument was filed in this office
 for record on the _____ day of _____ Oct 1979 _____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Wayne O. Harris
 OREGON
 MAY 6, 1955
 WAYNE O. HARRIS
 346