

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

This corner was established in 1880 by Edward W. Sanderson, under General Land Office Contract No. 368.

Surveyor General's records state:

Set post in stone mound from which:

A pine 14" dia. bears N70°W 70 lks.
A Fir 16" dia. bears S40°E 52 lks.



Description of corner evidence found:

Found a mound of stone.

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2"x30" G.I. pipe with a 2-1/2" brass cap mkd:

Exposed 12" in a mound of stone


I mark a D. Fir 10" dia. bears N53°10'E 20.7 feet T6S, R26E, S31 BT
I mark a D. Fir 6" dia. bears N36°12'W 82.2 feet T6S, R25E, S36 BT

Monument set 4/25/81.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kurt C. Weaver

OREGON
JULY 14, 1978
KURT C. WEAVER
1679



Office of.....**Surveyor**..... County of.....**Grant**.....
State of.....**Oregon**....., I hereby certify that the within instrument was filed in this office
for record on the 25 day of Oct, 1981.
Robert D. Dwyer by
(COUNTY OFFICIAL) (DEPUTY)