


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey
Section 36, T.7S., R.26E., W.M.

Z-23

History of original corner establishment:

Alonzo Gesner, under G.L.O. contract number 266,
dated June 20, 1877, set a stone 16"X 14"X 10"
and raised a stone mound at the corner.



Description of corner evidence found:

I found a stone 15"X 12"X 9", with no marks visible, in a stone mound; rusted tag on a Juniper NEly of the corner. Line tree to the east reasonably fits record distance.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the original corner point I set a 2 1/2"X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I buried the original stone alongside and built a stone mound around the monument.

T7S R26E
 $\frac{1}{4}$ S36
 $\frac{1}{4}$ S1
T8S
PLS 1832
1985

From the corner:

A Ponderosa Pine, 10" dia., N51°W, 64.3 ft.; marked: $\frac{1}{4}$ S36 BT
A Ponderosa Pine, 12" dia., S40 1/4°W, 32.5 ft.; marked: $\frac{1}{4}$ S1 BT

BTs have blaze and a 6" stripe painted red, a BT tag, an "Attention" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with an "Attention" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 17°E.

October 27, 1985

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro
OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832

Office of..... *Surveyor* County of..... *Grant*
State of..... *Oregon* I hereby certify that the within instrument was filed in this office
for record on the..... *29*..... day of..... *Jan*....., 19..... *85*.....
..... *Robert P. Dyer* by.....
(COUNTY OFFICIAL) (DEPUTY)