


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey
Section 36, T.7S., R.26E., W.M.

History of original corner establishment:

Alonzo Gesner under G.L.O. contract number 266, dated June 20, 1877, surveyed the north line of T.8S., R.26E. Running N89° 44'E on the north line of Section 11 of that township (south line of Section 36), he called a Yellow Pine, 20" dia., at 70.30 ch.



Description of corner evidence found:

I found a Ponderosa Pine, 28" dia., with healed double hacks on the east and west sides.

Description of monument and accessories I established to perpetuate the original location of this corner:

I painted a 6" red band around the line tree and attached a BT tag and an "Attention" sign.

I marked BTs to reference this angle point. From the line tree:

- AA Ponderosa Pine, 17" dia., N57°E, 75.3 ft.; marked: AP S36 BT
- A Ponderosa Pine, 17" dia., S27°E, 18.0 ft.; marked: AP S11 BT

BTs have blaze and a 6" band painted red, a BT tag, an "Attention" sign and an alum. "PLS-1832" washer nailed to the bottom of the blaze.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 17°E.

July 12, 1986



Office of Surveyor County of Grant
 State of Oregon I hereby certify that the within instrument was filed in this office
 for record on the 25 day of July, 1986
Robert D. Bayart by _____
 (COUNTY OFFICIAL) (DEPUTY)